



PERFORM 7500 T

PORTABLE POWER

Generating Sets Range PERFORM

PRODUCT ADVANTAGES

- · Entire group guaranteed 3 years
- KOHLER air-cooled industrial engine
- Compact frame with protection panels against shocks
- Good value for money
- Starting up facilitated thanks to the summer/winter positions

QUAD CLEAN AIR FILTER The Cyclonic Quad Clean air filters provide 4 levels of filtration which effectively filter out large particles and capture the finest particles. They ensure a continuous supply of clean air to the engine, fuel economies, increase the engine performance and extend its lifetime

OVERSIZED ALTERNATOR The oversized alternator is ideal for supplying electronic equipment and secures the engines sypplying . It has very low harmonic current and limits the voltage and frequency variation of the power supplied as well as handling high surge loads.

Range PERFORM

An efficient, cost effective and easy to handle equipment, suitable for frequent use.





















PERFORM 7500 T

GENERAL SPECIFICATIONS

Range	PERFORM
Frequency (Hz)	50 Hz
Max power (kW) *	6.50
Max power (kVA)	8.10
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Tank (L)	7.30
75% cons. (I/h) *	2.60
75% Autonomy (h) *	2.80
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69

ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	CH440
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	429
Oil system capacity including filters (L)	1.30

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	Н

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	55.50
Height (cm)	59
Dry Weight (kg)	93.50

PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56.50
Height (cm)	60
Weight (kg)	95.50
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	583



This product meets the Qualigen charter, which aims to elevel of quality and guarantee the safety of users. Qualig commitment to safety and quality.





PERFORM 7500 T

ACCESSORIES SUPPLIED



Funnel

Floor maintaining slot

RBAC

User and maintenance manual

Ergonomic handle grip



R03 This set includes the hour meter and the differential circuit breaker. **RKB1HD** Trolley kit for the generating sets of 6kW or below RKS2 Maintenance kit for KOHLER CH395 and CH440 engines. RH1 Cover for SDMO 's generating sets, welding sets and water pumps Male plugs for all models made up of: 2 x 16 A/230 V, EEC17: 1 x **RPM** 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V For earthing your generator set. Galvanised 1 m long spike, **RPQ** supplied with 2 m of 10 mm² cable.



Removable storage box