



VX 200/5H AM

PORTABLE POWER

Welding Sets Range WELDARC INTENS

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Entire group guaranteed 3 years
- Light storage box integrated
- Solid and high-performance equipment
- Auxiliary Single phase output

Range WELDARC INTENS

Welding sets which can be used on sites where there is no electricity.



VX 200/5H AM

WELDING SET SPECIFICATIONS

Range	WELDARC INTENS
Frequency (Hz)	60 Hz
Max power (kW) *	4
Max power (kVA)	4
Normal duty cycle 35% (A)	200
Intensif duty cycle 70% (A)	170
Stricking volts (V)	75
Rods diameter mini (mm)	1.6
Rods diameter maxi (mm)	4
Fuel	Petrol
Tank (L)	6.10
75% cons. (l/h) *	2.80
75% Autonomy (h) *	2.20
Sound power level guaranteed LwA dB(A)	
Acoustic pressure level @1m in dB(A)	92
Acoustic pressure level @7m in dB(A)	78

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX390
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	389
Oil system capacity including filters (L)	1.10

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 21
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

1 115V 20A socket (L5-20R GFCI) - circuit breaker + 1 115V 30A socket (L5-30R) - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	87
Width (cm)	57
Height (cm)	55.50
Dry Weight (kg)	86

PACKAGING

Packaging type	Box / Pallet
Length (cm)	88
Width (cm)	58.50
Height (cm)	70
Weight (kg)	99
Pallet type	
Number of box by pallet	0
Pallet height (cm)	0
weight of the packaged Pallet (kg)	0



4/4/2018

VX 200/5H AM - PORTABLE POWER - Welding Sets WELDARC INTENS

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



Storage box



User and maintenance manual

OPTIONS



RKB2

Trolley kit for the generating sets superior to 6kW



RBH1

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RH2

Cover for SDMO 's generating sets, welding sets and water pumps