



# ST 2.36 H

PORTABLE POWER

Water Pumps Range AQUALINE INTENS

#### **PRODUCT ADVANTAGES**

- HONDA Professional Engine
- Automatic priming
- Offeres accessories

#### Range AQUALINE INTENS

Designed for water with low solid content.















# ST 2.36 H

## WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Clear water with little sediment pump
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	600
Outlflow maximum (m3/h)	36
Lifting height (m)	29
Suction height (m)	8
<b>Granulometry (mm)</b>	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	2
75% cons. (I/h) *	1
75% Autonomy (h) *	2
Sound power level guaranteed LwA dB(A)	103
Acoustic pressure level @1m in dB(A)	87
Acoustic pressure level @7m in dB(A)	72

# **ENGINE SPECIFICATIONS**

Engine brand	HONDA
Engine ref.	GX120
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	118
Oil system capacity including filters (L)	0.60

### **DIMENSIONS AND WEIGHT**

Length (cm)	46.80
Width (cm)	36.20
Height (cm)	38
Dry Weight (kg)	23

#### **PACKAGING**

Packaging type	Box
Length (cm)	48.50
Width (cm)	38.50
Height (cm)	40
Weight (kg)	24.50
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	133
weight of the packaged Pallet (kg)	304





# **ACCESSORIES SUPPLIED**



Inlet filter

**RHO** 

**R11** 



Circlips



Screw-on connectors

User and maintenance manual





RBH1 Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



**RBH0-5** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



Cover for SDMO 's generating sets, welding sets and water pumps



Piping kit for 2 water pumps made up of 5m suction + 25m lift.

