



VX 200/4H

PORTABLE POWER

Welding Sets Range WELDARC INTENS

PRODUCT ADVANTAGES

- · HONDA Professional Engine
- Entire group guaranteed 3 years
- · Light storage box integrated
- Solid and high-performance equipment
- · Auxiliary Single phase output

Range WELDARC INTENS

Welding sets which can be used on sites where there is no electricity.











VX 200/4H

WELDING SET SPECIFICATIONS

| Range | WELDARC INTENS |
|--|----------------|
| Frequency (Hz) | 50 Hz |
| Max power (kW) * | 4 |
| Max power (kVA) | 4 |
| Normal duty cycle 35% (A) | 200 |
| Intensif duty cycle 70% (A) | 170 |
| Stricking volts (V) | 75 |
| Rods diameter mini (mm) | 1.6 |
| Rods diameter maxi (mm) | 4 |
| Fuel | Petrol |
| Tank (L) | 6.10 |
| 75% cons. (I/h) * | 2.50 |
| 75% Autonomy (h) * | 2.40 |
| Sound power level guaranteed LwA dB(A) | 97 |
| Acoustic pressure level @1m in dB(A) | 83 |
| Acoustic pressure level @7m in dB(A) | 69 |

ENGINE SPECIFICATIONS

| Engine brand | HONDA |
|---|---------|
| Engine ref. | GX390 |
| Distribution | O.H.V. |
| Start | Starter |
| Oil shutdown | Oui |
| Displacement (cm3) | 389 |
| Oil system capacity including filters (L) | 1.10 |

ALTERNATOR SPECIFICATIONS

| Technology | Collar and brush |
|--------------------------|------------------|
| AVR Regulation | No |
| Indication of protection | IP 23 |
| Insulation class | Н |

PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

DIMENSIONS AND WEIGHT

| Length (cm) | 88 |
|-----------------|-------|
| Width (cm) | 57 |
| Height (cm) | 55.50 |
| Dry Weight (kg) | 87 |

PACKAGING

| Packaging type | Box / Pallet |
|------------------------------------|--------------|
| Length (cm) | 88 |
| Width (cm) | 58.50 |
| Height (cm) | 70 |
| Weight (kg) | 100 |
| Pallet type | |
| Number of box by pallet | 0 |
| Pallet height (cm) | 0 |
| weight of the packaged Pallet (kg) | 0 |





VX 200/4H

ACCESSORIES SUPPLIED



Storage box



User and maintenance manual

OPTIONS



